

## FORESTRY MULCHERS FOR EXCAVATORS

# BLI/EX - BLI/EX/VT

### Forestry mulcher with Bite Limiter technology.

F AE introduces a new line of professional mulchers for excavators equipped with Bite Limiter technology. Special steel limiter rings limit the depth of blade action, reducing the demand for power, guaranteeing speed and exceptional performance. The BLI/EX - BLI/EX/VT (for 4-7.5 t excavators) has a 31 in working width and can mulch logs up to 5 in diameter.


The piston engine (with manually controlled variable displacement) makes it easy to use this mulcher on different excavators with different oil flow rates. The BLI/EX-BLI/EX/VT has a rotor equipped with a heat-treated forged steel tooth holder, together with Type Mini BL blades. This light, compact mulcher is easy to maneuver and perfect for various types of forestry work.



 13-37 gal/min


 Ø 5 in max

 4-7.5 t



**Hydraulic front trap door**  
helps contain debris and achieves finer sizing (optional)

**Hydraulic piston motor with manual displacement control**  
integrated relief valve and anticavitation valve




**Custom made thumb bracket**  
to move and reposition material



**Dedicated rear hood (deflector)**  
controls mulched material output for greater safety



**Bite Limiter rotor**  
special steel limiter rings control the depth of cut



## MAIN OPTIONS



**Attachment bracket**



**Excavator stand and thumb bracket**  
useful in moving material to be mulched



**Hydraulic front hood**  
for optimal mulching, reduces the ejection of mulched material

## STANDARD EQUIPMENT

17/34 cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (13-34 gpm) (BLI/EX)	Belt transmission
55/38 cc variable torque hydraulic piston motor (17-37 gpm) (BLI/EX/VT)	Bulkhead for hydraulic connections
Flow control system valve	Rear hood with mechanical adjustment
Safety and anticavitation valve	Rotor Bite Limiter
Enclosed / anti dust machine body	Dedicated rear hood (deflector)
Motor enclosed in the frame	

## OPTIONS

Customized setting hydraulic motor	Fixed thumb bracket
Diverter valve	Customized attachment bracket with pins
Hydraulic rear hood	Multiple tooth options
Hydraulic front hood for excavator AUX line	
Not supplied with hoses	Case drain required

MODEL	BLI/EX-75	BLI/EX/VT-75
<b>Flow rate</b> (gal/min)	13-34	17-37
<b>Pressure</b> (PSI)	2600-5080	2600-5080
<b>Excavator weight</b> (t)	4-7.5	4-7.5
<b>Working width</b> (in)	31	31
<b>Weight</b> (lbs)	783	783
<b>Rotor diameter</b> (in)	11.8	11.8
<b>Max shredding diameter</b> (in)	5	5
<b>No. blades</b> type MINI BL	14	14

*Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.*

## ROTOR TYPE BL



**BLADE MINI BL**  
(standard)

**MINI C/3**  
(option)