

FORESTRY MULCHERS FOR EXCAVATORS

PML/EX

Mulcher with hammer/flail rotor for excavators.

This mulcher can be equipped with a standard 27cc motor or an optional 38cc motor to mount to excavators ranging from 5.5 to 7.5 tons. There is also an optional 17/34cc variable manual displacement hydraulic motor with mechanical adjustment that makes this model

ideal for any excavator. The flow control valve ensures an easy and rapid mounting of the mulcher without adjustments or modifications to the hydraulic system of the excavator.

 17-34 gal/min

 Ø 2 in max

 5.5-7.5 t



Hydraulic hoses

Various types of hydraulic motors
to adapt to different models of excavators

Anti dust machine body



STANDARD EQUIPMENT

27 cc gear motor with integrated anticavitation valve (17-26 gpm)	Rear hood with mechanical adjustment
Flow control system valve (only for 27 cc and 38 cc motors)	Protection chains
Enclosed / anti dust machine body	Supporting service leg
Motor enclosed in the frame	Welded counterblades
Belt transmission	Rear roller
Hydraulic hoses	

OPTIONS

38 cc gear motor with integrated anticavitation valve (24-34 gpm)	Customized attachment bracket with pins
17/34 cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (11-32 gpm) (3600 psi)	Attachment plate with self levelling device
Customized setting hydraulic motor	Possibility to have the rotor equipped with PML hammers or Y-flails
Option 17/34 cc motor Case drain required	

MODEL	PML/EX 100	PML/EX 125	PML/EX 150
Flow rate (gal/min)	17-34	17-34	17-34
Pressure (PSI)	2600-3050	2600-3050	2600-3050
Excavator weight (t)	5.5-7.5	6.0-7.5	6.5-7.5
Working width (in)	40	49	59
Weight (lbs)	705	794	882
Rotor diameter (in)	14.2	14.2	14.2
Max shredding diameter (in)	2	2	2
No. hammers type PML	16	20	24
No. flails type Y/2	16	20	24

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS




Customized attachment bracket



Attachment plate with self levelling device
to adapt to all types of terrain



Possibility to have the rotor equipped with PML hammers or Y-flail



Customized setting hydraulic motor

